

PRODUKTDATENBLATT

Modellkennung(en)	10045429, 10045430				
Angabe	Symbol	Wert	Einheit	Angabe	Einheit
Wärmeleistung			Nur bei elektrischen Speicher-Einzelraumheizgeräten: Art der Regelung der Wärmezufuhr		
Nennwärmeleistung	P _{nom}	2,5	kW	Manuelle Regelung der Wärmezufuhr mit integriertem Thermostat	nein
Mindestwärmeleistung (Richtwert)	P _{min}	1,25	kW	Manuelle Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	nein
Maximale kontinuierliche Wärmeleistung	P _{max,c}	2,5	kW	Elektronische Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	nein
Hilfsstromverbrauch			Wärmeabgabe mit Gebläseunterstützung		nein
Bei Nennwärmeleistung	e _{l,max}	k.A.	kW	Art der Wärmeleistung/Raumtemperaturkontrolle	
Bei Mindestwärmeleistung	e _{l,min}	k.A.	kW	Einstufige Wärmeleistung, keine Raumtemperaturkontrolle	nein
Im Bereitschaftszustand	e _{l,SB}	0,00122	W	Zwei oder mehr manuell einstellbare Stufen, keine Raumtemperaturkontrolle	nein
			Raumtemperaturkontrolle mit mechanischem Thermostat	nein	
			Mit elektronischer Raumtemperaturkontrolle	nein	
			Mit elektronischer Raumtemperaturkontrolle und Tageszeitregelung	nein	
			Mit elektronischer Raumtemperaturkontrolle und Wochentagsregelung	ja	
			Sonstige Regelungsoptionen		
			Raumtemperaturkontrolle mit Präsenzerkennung	nein	
			Raumtemperaturkontrolle mit Erkennung offener Fenster	ja	
			Mit Fernbedienungsoption	ja	
			Mit adaptiver Regelung des Heizbeginns	nein	
			Mit Betriebszeitbegrenzung	ja	
			Mit Schwarzkugelsensor	nein	
Kontaktangaben	Chal-Tec GmbH, Wallstraße 16, 10179, Berlin, Deutschland				

PRODUCT DATA SHEET

Model identifier(s)	10045429, 10045430				
Specification	Symbol	Value	Unit	Specification	Unit
Heat output			Only for electric storage room heaters: Type of heat supply control		
Nominal heat output	P _{nom}	2.5	kW	Manual control of the heat supply with integrated thermostat	no
Minimum heat output (guide value)	P _{min}	1.25	kW	Manual control of the heat supply with feedback of the room and/or outside temperature	no
Maximum continuous heat output	P _{max,c}	2.5	kW	Electronic control of the heat supply with feedback of the room and/or outside temperature	no
Auxiliary power consumption			Heat output with fan support		no
Nominal heat output	e _{l,max}	N/A	kW	Type of heat output/room temperature control	
With minimum heat output	e _{l,min}	N/A	kW	Single stage heat output, no room temperature control	no
Standby mode	e _{l,SB}	0.00122	W	Two or more manually adjustable levels, no room temperature control	no
			Room temperature control with mechanical thermostat	no	
			With electronic room temperature control	no	
			With electronic room temperature control and time of day control	no	
			With electronic room temperature control and day of week control	yes	
			Other regulatory options		
			Room temperature control with presence detection	no	
			Room temperature control with open window detection	yes	
			With remote control option	yes	
			Adaptive control of heating	no	
			Operating time limit	yes	
			With black ball sensor	no	
Contact details	Chal-Tec GmbH, Wallstraße 16, 10179 Berlin, Germany.				